USTOM CAR

Arctic Ultraflex Blue® Eye-to-Eye and Battery Terminal Cables

Arctic Ultraflex Blue® Eye-to-Eye Cables

Eye-to-Eye Cables are commonly used for *grounds*, *starters*, *inverters*, and *batteries*. Built with Polar Wire's *Arctic Ultraflex Blue*® cable for superior flexibility and unbeatable performance. Fitted with heavy duty 3/8" plated copper eyelet lugs (*page 46*) in negative, positive, and series (negative-to-positive) configurations. Sealed with adhesive shrink



4 Gauge			
Part Number Negative	Positive	Series	Standard Length
SC-4-10N	SC-4-10P	SC-4-10S	10"
SC-4-14N	SC-4-14P	SC-4-14S	14"
SC-4-18N	SC-4-18P	SC-4-18S	18"
SC-4-24N	SC-4-24P		24"
SC-4-29N	SC-4-29P		29"
SC-4-36N	SC-4-36P		36"
SC-4-48N	SC-4-48P		48"
SC-4-60N	SC-4-60P		60"

Part Number Standard Negative Positive Series Length SC-20-12N SC-20-12P SC-20-12S SC-20-14N SC-20-14S 14" SC-20-14P SC-20-18N SC-20-18P SC-20-18S 18" SC-20-24N SC-20-24P 24" 36" SC-20-36N SC-20-36F SC-20-48N SC-20-48P 48" SC-20-60N SC-20-60P 60" SC-20-120P 120" SC-20-120N SC-20-180N SC-20-180P 180'

4/0 Gauge

2/0 Gauge

Part Number Negative	Positive	Standard Length
SC-40-36N	SC-40-36P	36"
SC-40-60N	SC-40-60P	60"
SC-40-72N	SC-40-72N	72"
SC-40-120N	SC-40-120P	120"
SC-40-180N	SC-40-180P	180"

THHW Flexible Golf Cart Cables



(NO ALUMINUM) fine stranded THHW flexible battery cable, for maximum conductivity and performance in heat conditions as high as 221°F!

Our Golf Cart Cables are fitted with Eco-Max® top mount copper battery terminals or heavy copper closed-end lugs, plated against corrosion, and properly sized for the required electrical load.

NO MORE MELTDOWNS from thin, inadequate fittings and inferior wire!

- Exceeds OEM quality and SAE automotive standards
- Rated 600 Volts, designed for 6V batteries in 24 and 36 Volt systems
- Ultra flexible cables install easily in cramped spaces and tight corners

4 Gauge Series Golf Cart Cables

Part Number	Terminals	Length
GC-4-9S-38	3/8" Plated Lugs	9"
GC-4-9S-516	5/16" Plated Lugs	9"
GC-4-9S-TM	Top Mount Terminals	9"
GC-4-12S-38	3/8" Plated Lugs	12"
GC-4-12S-516	5/16" Plated Lugs	12"
GC-4-12S-TM	Top Mount Terminals	12"
GC-4-20S-38	3/8" Plated Lugs	20"
GC-4-20S-516	5/16" Plated Lugs	20"

Series: Black cable, red heat shrink on positive end, black on negative end



Call us to create a custom cable set for your specific golf cart!

Arctic Ultraflex Blue® Battery Terminal Cables

4 Gauge Top Mount

1204 TEW 105°C 600V FT1

Part Number Negative	Positive	Cable Length
TM-4-10N	TM-4-10P	10"
TM-4-14N	TM-4-14P	14"
TM-4-16N	TM-4-16P	16"
TM-4-20N	TM-4-20P	20"
TM-4-23N	TM-4-23P	23"
TM-4-26N	TM-4-26P	26"
TM-4-28N	TM-4-28P	28"
TM-4-32N	TM-4-32P	32"
TM-4-36N	TM-4-36P	36"
TM-4-42N	TM-4-42P	42"
TM-4-45N	TM-4-45P	45"
TM-4-55N	TM-4-55P	55"

2 Gauge Top Mount

Part Number Negative	Positive	Cable Lengths
TM-2-20N	TM-2-20P	20"
TM-2-25N	TM-2-25P	25"
TM-2-30N	TM-2-30P	30"
TM-2-35N	TM-2-35P	35"
TM-2-40N	TM-2-40P	40"
TM-2-45N	TM-2-45P	45"
TM-2-50N	TM-2-50P	50"
TM-2-55N	TM-2-55P	55"
TM-2-60N	TM-2-60P	60"
TM-2-65N	TM-2-65P	65"
TM-2-70N	TM-2-70P	70"
TM-2-78N	TM-2-78P	78"

2/0 Gauge Top Mount

Part Number Negative	Positive	Cable Lengths
TM-20-18N	TM-20-18P	18"
TM-20-24N	TM-20-24P	24"
TM-20-30N	TM-20-30P	30"
TM-20-36N	TM-20-36P	36"
TM-20-42N	TM-20-42P	42"
TM-20-48N	TM-20-48P	48"
TM-20-54N	TM-20-54P	54"
TM-20-60N	TM-20-60P	60"
TM-20-66N	TM-20-66P	66"
TM-20-72N	TM-20-72P	72"

Top Mount Terminal

4 Gauge Top Mount with lead

E196955 91 AWM

Part Number Negative	Positive	Cable Lengths
TML-4-15N	TML-4-15P	15"
TML-4-19N	TML-4-19P	19"
TML-4-25N	TML-4-25P	25"
TML-4-29N	TML-4-29P	29"
TML-4-36N	TML-4-36P	36"
TML-4-38N	TML-4-38P	38"
TML-4-45N	TML-4-45P	45"
TML-4-50N	TML-4-50P	50"
TML-4-55N	TML-4-55P	55"
TML-4-68N	TML-4-68P	68"
TML-4-78N	TML-4-78P	78"

4 Gauge Side Mount with lead

Part Number Negative	Positive	Cable Lengths
SML-4-20N	SML-4-20P	20"
SML-4-25N	SML-4-25P	25"
SML-4-30N	SML-4-30P	30"
SML-4-35N	SML-4-35P	35"
SML-4-40N	SML-4-40P	40"
SML-4-45N	SML-4-45P	45"
SML-4-50N	SML-4-50P	50"
SML-4-55N	SML-4-55P	55"
SML-4-60N	SML-4-60P	60"
SML-4-65N	SML-4-65P	65"

2 Gauge Side Mount with lead

Part Number Negative	Positive	Cable Lengths
SML-2-20N	SML-2-20P	20"
SML-2-25N	SML-2-25P	25"
SML-2-30N	SML-2-30P	30"
SML-2-35N	SML-2-35P	35"
SML-2-40N	SML-2-40P	40"
SML-2-45N	SML-2-45P	45"
SML-2-50N	SML-2-50P	50"
SML-2-55N	SML-2-55P	55"
SML-2-60N	SML-2-60P	60"
SML-2-65N	SML-2-65P	65"
SML-2-70N	SML-2-70P	70"
SML-2-78N	SML-2-78P	78"

Polar Wire Battery Cables are stocked in our most popular styles and sizes to save you time and money. We build our battery cables with **Arctic Ultraflex Blue**® Arctic grade wire and Eco-Max® plated copper battery terminals (page 54) in color coded negative to negative and positive to positive configurations.

LIFETIME WARRANTY on manufacturing and materials.

Standard 12" lead is 12 AWG tinned **Arctic Ultraflex Blue**® wire.

Standard color configurations

Negative: Blue cable, black heat shrink, black lead **Positive:** Blue cable, red heat shrink, red lead

Go Ahead, Be Different!

You are not limited to our standard colors and lengths. We can make your cables in the specific configurations you need.

Special volume pricing—call us!







Side Mount Terminal