

FLEXO® PET (PT) Braided Sleeving

is used in electronics, automotive, marine and industrial wire harnessing applications where cost efficient and durability are critical. The unique braided construction and wide expandability—up to 150%—allows quick and easy installation over large connectors and long runs. PT can be found in applications ranging from small office/home office to high tech wire and cable harnesses.

PT is braided from 10mm polyethylene terephthalate (PET) monofilament yarns. The material has an operating temperature range of -75°C (-103°F) to 125°C (257°F), and is resistant to chemical degradation, UV radiation, cuts and abrasions.

General Purpose Braided Sleeving									
Part Number	Nominal Size	Expansion Min Range	Expansion Max Range	Spool Size	Available Colors				
PET18-BB	1/8"	3/32"	1/4"	225'	All 19 colors pictured below				
PET14-BB	1/4"	1/8"	7/16"	200'	All 19 colors pictured below				
PET38-BB	3/8"	3/16"	5/8"	125'	All 19 colors pictured below				
PET12-BB	1/2"	1/4"	3/4"	100'	All 19 colors pictured below				
PET58-BB	5/8"	3/8"	1"	100'	Red, White, Black, Carbon,				
					Green, Blue				
PET34-BB	3/4"	1/2"	1 1/4"	75'	All 19 colors pictured below				
PET1-BB	1"	5/8"	1 5/8"	65'	Purple, Blue, Black, Green, Gray, Red				
PET114-BB	1 1/4"	3/4"	1 3/4"	50'	All 19 colors pictured below				
PET112-BB	1 1/2"	1"	2 1/2"	40'	All 19 colors pictured below				
PET134-BB	1 3/4"	1 1/4"	2 3/4"	30'	All 19 colors pictured below				
PET2-BB	2"	1 1/2"	3 1/2"	50'	All 19 colors pictured below				
PET212-BB	2 1/2"	1 3/4"	4 1/2"	50'	All 19 colors pictured below				
PET3-BB	3"	2 1/2"	4 3/4"	50'	All 19 colors pictured below				

TO ORDER, add desired color code (BB) to the part number. Example: PET18-RD



and cleanly with a hot knife and once installed, will beautify and protect any wire, hose or cable application.

Flexo® PET Pro-Pak



THIS BOX CONTAINS

Flexo F6® Wrappable Split Braided Tube

Flexo F6® has a unique split, semi-rigid braided construction

that makes it the ideal solution where ease of installation is of primary importance.

The lateral split allows the tube to open up to accommodate a wide variety of bundling requirements, and the semi-rigid braid simply closes around the entire installation without the need for any additional fasteners.

The 10 mm PET braid is lightweight, quiet and flexible. The 25% edge overlap (at nominal diameter) allows coverage around inline plugs, connectors and splices. F6 will bend to a tight radius without distorting or splitting open. And, unlike full rigid tubing, F6 will not impair or affect the flexibility of harnesses.

Large 25% edge overlap allows easy installation over splices and inline connectors without exposing wires and cables

F6 Semi-Rigid Split Braid

CMPLET	Part Number FLEXO-18 FLEXO-14 FLEXO-38 FLEXO-12 FLEXO-34 FLEXO-11 FLEXO-112 FLEXO-2	Nominal Size 1/8" 1/4" 3/8" 1/2" 3/4" 1" 1 1/2" 2"	Package Quantity 100' 100' 75' 50' 50' 25' 25'	
Dispenser Box Packaging				
			quantiti vailable	es