

Pro Grade PVC Electrical Tape

StrongHold™ Professional Grade Electrical Tape is a 7 mil non-corrosive, pressure sensitive vinyl electrical tape that provides high abrasion resistance with easy application over a range of temperatures. Flame retardant and cold resistant, with excellent elasticity and insulating properties. High-elongation. Protects against abrasion, water, oil, and other corrosive chemicals. Suitable as primary insulation when splicing up to 600 Volts. Can be used as protective jacketing.

StrongHold™ Pro Grade Tape is offered in black (ST-43) and in nine colors for color coding (ST35). Packaged individually in clear plastic storage pucks.

- 7 mil thickness
- 0°F to 221°F (-18°C to 105°C)
- 260% elongation typ
- 30 N/cm breaking strength typ
- 2.2 N/cm sticking power typ (adhesion to steel at 72° F)



StrongHold ST43

3/4" x 66' x .007"
19mm x 20m x .177mm

Part Number Color
ST43 ● Black

StrongHold ST35

3/4" x 66' x .007"
19mm x 20m x .177mm

Part Number	Color
ST35-WHITE	○ White
ST35-GREEN	● Green
ST35-GRAY	● Gray
ST35-RED	● Red
ST35-VIOLET	● Violet
ST35-BLUE	● Blue
ST35-ORANGE	● Orange
ST35-BROWN	● Brown
ST35-YELLOW	● Yellow



General Purpose PVC Electrical Tape

StrongHold™ General Purpose PVC Electrical Tape is an economical 7 mil, high-elongation vinyl tape with non-corrosive, pressure sensitive rubber adhesive. Excellent conformability properties. Abrasion and weather-resistant. Excellent mechanical and electrical insulation properties. Wraps smoothly and holds tight over a wide temperature range. Suitable as primary insulation when splicing up to 600 Volts or 80°C (176°F).

StrongHold™ General Purpose comes in black (ST14) and in nine colors for color coding (ST17). Individual cellophane wrapped rolls.

- 7 mil thickness
- 14°F to 176°F (-10°C to 80°C)
- 200% elongation typ
- 25 N/cm breaking strength typ
- 1.6-1.8 N/cm sticking power typ (adhesion to steel at 72° F)



StrongHold ST14

3/4" x 60' x .007"
19mm x 18m x .177mm

Part Number Color
ST14 ● Black

StrongHold ST17

3/4" x 66' x .007"
19mm x 20m x .177mm

Part Number	Color
ST17-WHITE	○ White
ST17-GREEN	● Green
ST17-GRAY	● Gray
ST17-RED	● Red
ST17-VIOLET	● Violet
ST17-BLUE	● Blue
ST17-ORANGE	● Orange
ST17-BROWN	● Brown
ST17-YELLOW	● Yellow



Heavy Duty PVC Electrical Tape

StrongHold™ Heavy Duty PVC Electrical Tape applies easily and provides a high level of performance over a range of temperatures. Protects against abrasion, water, oil, and other corrosive chemicals. Flame retardant, UV resistant, cold resistant, non-corrosive, lead free. Suitable as primary insulation when used for splicing up to 600 Volts or 80°C (176°F) and can be used as protective outer jacket in low temperature applications.



- 8.5 mil thickness
- 0°F to 221°F (-18°C to 105°C)
- 300% elongation typ
- 30 N/cm breaking strength typ
- 2.2 N/cm sticking power typ (adhesion to steel at 72° F)



StrongHold ST88

3/4" x 66' x .0085"
19mm x 20m x .21mm

Part Number **Color**
ST88 ● Black

2" x 66' x .0085"
50.8mm x 20.1m x .021mm

Part Number **Color**
ST88-2 ● Black

Self-Fusing Silicone Tape

Wrap 'N Seal Self-Fusing Silicone Tape self fuses and cures in 24 hours to form a permanent, moisture-tight seal. Ideal for high temperature and marine use.

- Has no adhesive lining, applying cleanly with no sticky residue
- Center ridge acts as a wrapping guide for a uniform application



Wrap 'N Seal Tape

1" x 20'
25.4mm x 6.1m

Part Number **Color**
SW-BLK ● Black
SW-WHT ○ White
SW-GRN ● Green
SW-GRY ● Gray
SW-RED ● Red
SW-BLU ● Blue
SW-ORG ● Orange
SW-CLR ● Clear
SW-YEL ● Yellow
SW-GLO ○ Glow in the Dark

Sealant Tape

Canusa® CTSB-2 Rubber Based Sealant Tape is specially designed for use with heat shrink tubing. This nonconductive material softens to fill voids, provides a superior waterproof seal, remains flexible over time, and provides excellent adhesion to PVC, PE, and steel.



Canusa® CTSG-1 Sealant Tape is a crosslinked, gray butyl tape suitable for continuous high temperature applications. This nonconductive material environmentally seals areas and tubing, smooths transitions and protects sharp edges, and is resistant to common fluids and solvents.



CTSB-2 Sealant Tape

2" x 25'
50.8mm x 7.62m

Part Number **Color**
CTSB-2 ● Black

CTSG-1 Sealant Tape

1" x 25'
25.4mm x 7.62m

Part Number **Color**
CTSG-1 ● Gray