

DC Power Plugs and Receptacles

12V High AMP Trolling Motor Plugs, Receptacles, and Covers ConnectPro® Motor Trolling Plugs and Receptacles feature o-ring seals, weather resistant plug covers and sealing caps for waterproof connections. Exclusive marine grade turn-locking connection 2-Wire Plug Weather resistant seals and covers safeguard 12VBPS2 12VBPS2 and 12VBRS2 2-Wire electrical contacts from water and corrosion also sold as a set Receptacle 12VBRS2 • Universal design works with 12, 24, 12/24, Set Part Number 12VCPS2 24/36, and 36 Volt 2 or 3 wire systems Plating protects brass electrical contacts Cover 300251 for two or three wires from power robbing corrosion · Soft contoured plug cover keeps away 3-Wire Plug dirt and moisture, makes hook-ups 12VBP and blade alignment easy 3-Wire · Accepts up to 8 AWG wire Receptacle 12VBR Receptacle mounts in standard 1-1/8" hole from front or rear, 12VBP and 12VBR Cover 300297 mounting plate included also sold as a set for single wire up Set Part Number 12VCP • Easy install—no crimping, shrink or tape needed to 1/2" diameter 12V Marine Grade Plug and Receptacle · Corrosion resistant marine grade construction Receptacle mounting plate included Plug Watertight receptacle cap 12VPG • Plug features LED power indicator

AC Power Inlets and Covers

125V Power Inlets

· Easy to install

- Durable corrosion and UV resistant construction
- Easy to install
- · Increases security
- · Water-tight cap
- Great for 5th wheels, trailers, and campers
- UL Listed and CSA Certified









Receptacle

12VRC

12VPG and 12VRC

also sold as a set

Set Part Number 12VPK

AC Plugs and Connectors

Illuminated, standard, and corrosion resistant 3-wire Plugs and Connectors in 15, 20, and 30 AMPS. Straight blade and locking styles.

Features

- Tough ribbed nylon housing resists corrosion and a wide range of chemicals
- 15A and 20A accept #18 to #10 gauge wires
- · Solid brass blades, contacts, terminal screws
- Single piece, rivetless contact design means less chance for resistance and heat rise
- Open terminals, close-in wire entrance holes and generous wiring space for easy wiring
- Internal cord clamp insert allows use of greatest range of cord sizes
- Designed with the installer in mind to minimize labor and ensure ease of assembly

ConnectGlow Devices

- Bright neon bulb with full 360° visibility lights up when a circuit is energized
- Mag-Vu[™] window magnifies bulb and terminal for easy inspection
- 5 year limited warranty

Corrosion Resistant Devices

- Marine grade construction
- Exclusive cover provides waterproof seal
- Nickel plated blades and contacts with stainless steel screws for excellent conductivity in corrosive environments
- Independent lab certified corrosion resistant per 240-hour 5% salt spray test in accordance with ASTM B117
- 5 year limited warranty

Applications

- Power-driven hand tools
- Electrical industrial equipment
- Temporary taps at construction sites
- Staging and entertainment equipment
- Broadcast studio equipment
- Hospital/healthcare equipment
- Fire-protection equipment
- Manufacturing plants
- Shore power cables

More sizes and styles online!

ConnectGlow Illuminated 3-Wire Plugs and Connectors Clear Housing

Connector Part Number	Plug Part Number	AMPS	Poles/Wires	Volts	Blade Style	Nema Configuration
5269L	5266L	15	2P / 3W	125	Straight	5-15R 🗓 🚺 5-15P
4729L	4720L	15	2P / 3W	125	Locking	L5-15R 🕠 🗘 L5-15P
205CL	205PL	20	2P / 3W	125	Locking	L5-20R



5269L







4720L



205CL



Standard Non-Lighted 3-wire Plugs and Connectors

Black Housing

Connector Part Number	Plug Part Number	AMPS	Poles/Wires	Volts	Blade Style	Nema Configuration
5269N	5266N	15	2P / 3W	125	Straight	5-15R 🗓 🚺 5-15P
5369N	5366N	20	2P / 3W	125	Straight	5-20R 🖫 🖜 5-20P
305C	305P	30	2P / 3W	125	Locking	L5-30R









5369N





5366N





Corrosion Resistant 3-wire Plugs and Connectors

Yellow Housing

Connector Part Number	Plug Part Number	AMPS	Poles/Wires	Volts	Blade Style	Nema Configuration
5269CRV	5266CR	15	2P / 3W	125	Straight	5-15R 🗓 🚺 5-15P
5369CRV	-	20	2P / 3W	125	Straight	5-20R 🕝 🕥 5-20P
305CRCN	305CRPN	30	2P / 3W	125	Locking	L5-30R





5269CR



5266CR



5369CR



